

Tenda AC8 AC1200 wireless dual band ruter 2.4+5GHz

## Tenda AC8 AC1200 wireless dual band ruter 2.4+5GHz, 1W/3L, Gbit, 1Ghz cpu 128mb, 4x6dBi 9V/1A

Šifra: 18849  
Kategorija proizvoda: Ruteri  
Proizvođač: Tenda

**Cena: 4.679,00** din.

AC8 is a dual band gigabit wireless router specially designed for family with fibre access. Equipped with gigabit ports to support up to 1000 Mbps bandwidth access. The dual band provide 1167Mbps frequency, fully utilise the gigabit fibre. This router is equipped with 28nm 1 GHz CPU to provide better performance. The integrated dual-band technology combines both 2.4GHz and 5GHz under one Wi-Fi name; The 5GHz frequency band is set as priority and faster signal frequency would be allocated to you automatically by our dynamic optimization system. New designed 6 dBi antennas, meet the coverage requirement for small and medium household. AC8 also support broadband account automatic transfer and other features

Standard&Protocol IEEE802.3, IEEE802.3u, IEEE802.3ab Interface 1\*10/100/1000Mbps WAN port 3\*10/100/1000Mbps LAN ports Antenna 4\*6dBi external dual band antennas Button 1\*WPS/Reset button Power Input: AC 200-240V—50/60Hz Output: DC 9V 1A LED indicator 1\*LED Dimension 200x127x33.6mm(L\*W\*H) Wireless Standards IEEE 802.11ac/a/n @5GHz IEEE 802.11b/g/n @2.4GHz Data Rate 2.4GHz: 300Mbps 5GHz: 867Mbps Frequency 2.4GHz & 5GHz Wireless Security WPA-PSK/WPA2-PSK, WPA/WPA2 Wireless Security : Enable /Disable Internet Connection Type PPPoE, Dynamic IP, Static IP Support automatic access detection Supports broadband account automatic transfer Operating Mode Wireless Router Mode AP Mode Universal Repeater mode WISP Mode DHCP DHCP Server DHCP Client List DHCP Reservation Virtual Server Port Forwarding DMZ Host UPnP Security Client Filter(supports black list and white list) Parental Control(supports black list and white list) Remote Web Management Firewall Forbid WAN PING from internet DDNS Support DynDNS, 88ip Other Function Broadband management MAC address clone Static Routing System Log Backup & Restore configurations Firmware upgrade from local Temperature Operating Temperature: 0? ~ 40? Storage Temperature: -40? ~ 70?. Humidity Operating Humidity: 10% ~ 90% RH non-condensing Storage Humidity: 5% ~ 90%RH non-condensing. Default Settings Default Access: tendawifi.com or http://192.168.0.1 Certification CE, FCC, CCC, SRRC Package Content Wireless Router\*1 Gigabit Ethernet Cable\*1 Power Adapter\*1 Installation Guide\*1