

## Cudy GS105 metalni GS105D 5-Port Gbit Desktop Switch, 5x RJ45 10/100/1000

Cudy GS105 metalni GS105D 5-Port Gbit Desktop Switch

Šifra: 38419  
Kategorija proizvoda: Switch uredjaji  
Proizvođač: Cudy

**Cena: 1.097,00 din.**

-Complies with IEEE 802.3, IEEE 802.3u, IEEE802.3x and IEEE 802.3ab standards -5 10/100/1000Mbps Auto-Negotiation, Auto-MDI/MDIX ports provide smart switching between 10Mbps, 100Mbps and 1000Mbps hardware -Non-blocking switching architecture enables full wire-speed packets forwarding and filtering - Store-and-Forward switching method -Supports 16K MAC address auto-learning and auto-agin Standard configurati: 5 10/100/1000M RJ-45 adaptive ports Switching Capacity: 10Gbps Throughput: 7.44Mpps Packet Buffer: 1M MAC Address: 1K Jumbo Frame: 2K Transfer Mode: Store and forward MTBF: 100000 hour Network protocol: IEEE802.3 (10Base-T) IEEE802.3u (100Base-TX) IEEE802.3ab (1000Base-TX) IEEE802.3x (Flow control) Industry Standard EMI: FCC Part 15 CISPR (EN55032) class A EMS: EN61000-4-2 (ESD)?EN61000-4-4 (EFT) Shock: IEC 60068-2-27 Free Fall: IEC 60068-2-32 Vibration: IEC 60068-2-6 Network Medium 10Base-T : Cat3,4,5 or above UTP(=100m) 100Base-TX : Cat5 or above UTP(=100m) 1000Base-TX : Cat5 or aboveUTP(=100m) Working Temperature:-10~50°C Storage Temperature:-40~70°C Working Humidity :10%~90%,non-condensing Storage Temperature:5%~90%,non-condensing Working Height:Maximum10,000 feet Storage heigh:Maximum 10,000 feet LED Indicators PWR(Power indicator)?Link(Network Link)?LOOP(Loop alarm) DIP Switch VLAN:Port Isolation, 1-4 ports are isolated each other, all communicate with uplink port 5; Default:Default mode, Support loop alarm; Extend:Monitor Mode, 1-4 ports support 100M speed reduction negotiation, support 250 meters in 10Mbps/s mode, port 7 and port 8 as uplink port Product Size:100\*70\*26mm Package Size:175\*120\*63mm Product Net-Weight:0.2kg Product Gross-Weight:0.4kg