

logo not found or type unknown

Firma: Laptop Centar d.o.o.
Adresa: Maglajska 11
Telefon: 011/635-1212
Fax: 0116351212
PIB: 105777840
E-mail: prodaja@laptopcentar.co.rs

Cudy GS2008PS2 * 8-Port Layer 2 Managed Gigabit PoE Switch

Cudy GS2008PS2 * 8-Port Layer 2 Managed Gigabit PoE+ Switch with 2 Gigabit SFP Slots, 120W

Šifra: 38421

Kategorija proizvoda: Switch uređaji

Proizvođač: Cudy

Cena: **13.762,00** din.

-8 Gigabit POE Ports, 2 Gigabit Combo Ports, 1 Console Port -Compatible with IEEE802.3at and IEEE802.3af - Ethernet port supports 10/100/1000M adaptive -Fanless design, Natural Cooling, Compatible with 1U Rack Mount -Support PoE Power Management, PoE watchdog -Lightning Protection Surge: General Mode 6KV, Differential Mode 4KV, ESD 15KV AC INPUT: AC100-240V, 50/60Hz Ethernet Port: 8 x 10/100/1000Mbps PoE Port 2 x 1000Mbps SFP Port 1 x RJ45 Console Port Bandwidth: 20Gbps Packet Forwarding rate: 14.88Mpps DDR SDRAM: 128MB Flash Memory: 16MB Packet Buffer Memory: 4M MAC Address: 8K Jumbo frame: 9.6Kbytes VLANs: 4096 Network Protocols: IEEE 802.3: Ethernet MAC Protocol IEEE 802.3i: 10BASE-T Ethernet IEEE 802.3u: 100BASE-TX Fast Ethernet IEEE 802.3ab: 1000BASE-T Gigabit Ethernet IEEE 802.3z: 1000BASE-X Gigabit Ethernet (optical fiber) IEEE 802.3ad: Standard method for performing link aggregation IEEE 802.3x: Flow control IEEE 802.1ab: LLDP/LLDP-MED (Link Layer Discovery Protocol) IEEE 802.1p: LAN Layer QoS/CoS Protocol Traffic Prioritization (Multicast filtering function) IEEE 802.1q: VLAN Bridge Operation IEEE 802.1x: Client/Server Access Control and Authentication Protocol IEEE 802.1d: STP IEEE 802.1s: MSTP IEEE 802.1w: RSTP PoE protocol: IEEE802.3af (15.4 W) IEEE802.3at (30 W) Network Media 10BASE-T: Cat3, 4, 5 or above UTP(=100 M) 100BASE-TX: Cat5 or above UTP(=100 M) 1000BASE-TX: Cat5 or above UTP(=100 M) Multi-mode Fiber: 50/125, 62.5/125, 100/140um Single-mode Fiber: 8/125, 8.7/125, 9/125, 10/125um Operating temperature: -20~50°C Storage temperature: -40~85°C Operating Humidity: 10%~90%, No condensation Storage Humidity: 5%~90%, No condensation Working height: Up to 10,000 feet Storage height: Up to 10,000 feet Indicator: PWR, SYS, SW, PoE, Link/ACT

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virtumanski - bezgotovinski.