

LAN Switch TP-LINK TL-SG1005P 101001000 5port (4 PoE)

Šifra: 44003
 Kategorija proizvoda: Switch uređaji
 Proizvođač: TP-LINK

Cena: **6.388,00** din.

HARDWARE FEATURES	
Interface	• 5 × 10/100/1000Mbps RJ45 Ports • AUTO Negotiation • AUTO MDI/MDIX
Network Media	• 10BASE-T: UTP category 3, 4, 5 cable (maximum 100m) • EIA/TIA-568 100Ω STP (maximum 100m) • 100BASE-TX: UTP category 5, 5e cable (maximum 100m) • EIA/TIA-568 100Ω STP (maximum 100m) • 1000BASE-T: UTP category 5, 5e, 6 or above cable (maximum 100m) • EIA/TIA-568 100Ω STP (maximum 100m)
Fan Quantity	Fanless
External Power Supply	External Power Adapter (Output: 53.5 VDC / 1.31 A)
Packet Forwarding Rate	7.44 Mpps
PoE Ports (RJ45)	• Standard: 802.3 af/at compliant • PoE Ports: Ports 1-4 • Power Supply: 65 W
Mac Address Table	2K
Jumbo Frame	16 KB
Switching Capacity	10 Gbps
Dimensions (W x D x H)	3.9×3.9×1.0 in (99.8×98×25 mm)
Max Power Consumption	• 4.29 W (220/50 Hz. no PD connected) • 74.24 W (220/50 Hz. with 65 W PD connected)
Max Heat Dissipation	• 14.63 BTU/h (no PD connected) • 253.16 BTU/h (with 65 W PD connected)
SOFTWARE FEATURES	
Advanced Features	• Compatible With IEEE 802.3af/at Compliant PDs • Mac Address Auto-Learning And Auto-Aging • IEEE 802.3x Flow Control • 802.1p/DSCP QoS • IGMP Snooping
Transfer Method	Store-And-Forward
OTHERS	
Certification	FCC, CE, RoHS
Package Contents	• TL-SG1005P • Power Adapter • Installation Guide
Environment	• Operating Temperature: 0-40 ° (32-104 °); • Storage Temperature: -40-70 ° (-40-158 °) • Operating Humidity: 10-90% RH non-condensing • Storage Humidity: 5-90% RH non-condensing