

## Napajanje Thermaltake 650W Smart BM2 12cmFan80PlusModular, PS-SPD-0650MNFABE-1

Napajanje Thermaltake 650W Smart BM2 12cmFan80

Šifra: 44025  
Kategorija proizvoda: Napajanja  
Proizvođač: Thermaltake

Cena: **10.598,00** din.

<b>P/N</b>	PS-SPD-0650MNFABU-1
<b>WATTS</b>	650W
<b>RGB FAN</b>	No
<b>MODEL</b>	SP-650AH3CCB-B   SP-650AH3CLB-B
<b>TYPE</b>	ATX 12V v2.4 and EPS v2.92
<b>MAX. OUTPUT CAPACITY</b>	650W
<b>COLOR</b>	Black
<b>DIMENSION ( W / H / D )</b>	150mm(W) x 86mm(H) x 160mm(D)
<b>PFC (POWER FACTOR CORRECTION)</b>	Active PFC
<b>POWER GOOD SIGNAL</b>	100-500 msec
<b>HOLD UP TIME</b>	> 12msec at 80% of full load at 230Vac input
<b>INPUT CURRENT</b>	10A max.   6 - 12A
<b>INPUT FREQUENCY RANGE</b>	47Hz -63Hz
<b>INPUT VOLTAGE</b>	100V-240V~
<b>OPERATING TEMPERATURE</b>	0°C to +40°C   +5°C to +40°C
<b>OPERATING HUMIDITY</b>	20% to 90%,non-condensing   20% to 85%,non-condensing
<b>STORAGE TEMPERATURE</b>	-20 °C to +70 °C   -40 °C to +55 °C
<b>STORAGE HUMIDITY</b>	5% to 95%, non-condensing   10% to 95%, non-condensing
<b>COOLING SYSTEM</b>	140mm Fan: 2300 R.P.M. ± 10%
<b>EFFICIENCY</b>	Meet 80 PLUS®Bronze at 115Vac input.
<b>MTBF</b>	100,000 hrs minimum
<b>SAFETY APPROVAL</b>	cTUVus/TUV/CE/FCC/S-mark/EAC/BSMI/C-TICK/CCC
<b>PCI-E 6+2PIN</b>	4
<b>PROTECTION</b>	OVP ,OPP, OCP, OTP