

logo not found or type unknown

Firma: Laptop Centar d.o.o.
Adresa: Maglajska 11
Telefon: 011/635-1212
Fax: 0116351212
PIB: 105777840
E-mail: prodaja@laptopcentar.co.rs

MB Gigabyte AMD AM4 A520M DS3H V2 1.0

MB Gigabyte AMD AM4 A520M DS3H V2 1.0

Šifra: 44224
Kategorija proizvoda: Matične ploče
Proizvođač: GIGABYTE

Cena: **8.616,00** din.

CPU

AMD Socket AM4,
support for: AMD
Ryzen™ 5000 Series/
Ryzen™ 5000 G-Series/
Ryzen™ 4000 G-Series
and Ryzen™ 3000 Series
Processors

(Please refer "CPU Support List" for more information.)

Chipset

AMD A520

Memor

4 x D
supp
(32 G
capac
mem

Onboard Graphics

Integrated Graphics Processor:

1 x DisplayPort,
supporting a maximum
resolution of
5120x2880@60 Hz*
Support for DisplayPort
1.4 version, HDCP 2.3,
and HDR.

1 x HDMI port,
supporting a maximum
resolution of
4096x2160@60 Hz*
Support for HDMI 2.1
version, HDCP 2.3, and
HDR.

Audio

Maximum shared memory of 16 GB

(Please
informa

Realtek® Audio CODEC

High Definition Audio
2/4/5.1/7.1-channel* You can change the functionality of an audio jack using the audio software. To configure 7.1-channel audio, access the audio software for audio settings.

LAN

Realtek® GbE LAN chip
(1 Gbps/100 Mbps)

Expans
1 x PCI
Supp
mode
1 x PCI
Supp
mode

Storage Interface

1 x M.2 connector, integrated in the CPU, supporting Socket 3, M key, type 2280 SSDs:

Supporting SATA and PCIe 3.0 x4/x2 SSDs

4 x SATA 6Gb/s connectors, integrated in the Chipset:

Supporting for RAID 0, RAID 1, and RAID 10

USB
CPU:
4 x U
on th
Chipse
2 x U
availa
intern
Back P
1 x P
keybo

Internal I/O Connectors

1 x 24-pin ATX main power connector

1 x 8-pin ATX 12V power connector

1 x CPU fan header

1 x system fan header

1 x M.2 Socket 3 connector

4 x SATA 6Gb/s connectors

1 x front panel header

1 x front panel audio header

1 x USB 3.2 Gen 1 header

1 x USB 2.0/1.1 header

1 x Trusted Platform Module (TPM) header

1 x Clear CMOS jumper (2x6 pin, for the GC-TPM2.0_S module only)

I/O Controller

iTE® I/O Controller Chip

H/W M
Volta

BIOS

1 x 128 Mbit flash

Use of licensed AMI UEFI BIOS 1.0a, DMI 2.7, WfM 2.0, SM BIOS 2.7, ACPI 5.0

Unique
Supp
Availa
APP C
moth
Supp
each
also v
moth
speci
Easy
Syste

Viewer

Support for Q-Flash
Support for Xpress Install

Bundled Software
Norton® Internet
Security (OEM version)

LAN bandwidth
management software

Operat
Supp
64-bi

Form Factor
Micro ATX Form Factor;
24.4cm x 24.4cm