

logo not found or type unknown

Firma: Laptop Centar d.o.o.  
Adresa: Maglajska 11  
Telefon: 011/635-1212  
Fax: 0116351212  
PIB: 105777840  
E-mail: prodaja@laptopcentar.co.rs

## MB Gigabyte AMD AM4 A520M DS3H V2 1.0

MB Gigabyte AMD AM4 A520M DS3H V2 1.0

Šifra: 44224  
Kategorija proizvoda: Matične ploče  
Proizvođač: GIGABYTE

Cena: **8.570,00** din.

### CPU

AMD Socket AM4,  
support for: AMD  
Ryzen™ 5000 Series/  
Ryzen™ 5000 G-Series/  
Ryzen™ 4000 G-Series  
and Ryzen™ 3000 Series  
Processors

(Please refer "CPU Support List" for more information.)

### Chipset

AMD A520

### Memor

4 x D  
supp  
(32 G  
capac  
mem

### Onboard Graphics

#### Integrated Graphics Processor:

1 x DisplayPort,  
supporting a maximum  
resolution of  
5120x2880@60 Hz\*  
Support for DisplayPort  
1.4 version, HDCP 2.3,  
and HDR.

1 x HDMI port,  
supporting a maximum  
resolution of  
4096x2160@60 Hz\*  
Support for HDMI 2.1  
version, HDCP 2.3, and  
HDR.

### Audio

Maximum shared memory of 16 GB

(Please  
informa

Realtek® Audio CODEC

High Definition Audio  
2/4/5.1/7.1-channel\* You can change the functionality of an audio jack using the audio software. To configure 7.1-channel audio, access the audio software for audio settings.

LAN

Realtek® GbE LAN chip  
(1 Gbps/100 Mbps)

Expans  
1 x PCI  
Supp  
mode  
1 x PCI  
Supp  
mode

Storage Interface

1 x M.2 connector, integrated in the CPU, supporting Socket 3, M key, type 2280 SSDs:

Supporting SATA and PCIe 3.0 x4/x2 SSDs

4 x SATA 6Gb/s connectors, integrated in the Chipset:

Supporting for RAID 0, RAID 1, and RAID 10

USB  
CPU:  
4 x U  
on th  
Chipse  
2 x U  
availa  
intern  
Back P  
1 x PS  
keybo

Internal I/O Connectors

1 x 24-pin ATX main power connector

1 x 8-pin ATX 12V power connector

1 x CPU fan header

1 x system fan header

1 x M.2 Socket 3

connector

4 x SATA 6Gb/s

connectors

1 x front panel header

1 x front panel audio

header

1 x USB 3.2 Gen 1

header

1 x USB 2.0/1.1 header

1 x Trusted Platform

Module (TPM) header

1 x Clear CMOS jumper

(2x6 pin, for the GC-TPM2.0\_S module only)

I/O Controller

iTE® I/O Controller Chip

H/W M  
Volta

BIOS

1 x 128 Mbit flash

Use of licensed AMI UEFI BIOS 1.0a, DMI 2.7, WfM 2.0, SM BIOS 2.7, ACPI 5.0

Unique  
Supp  
Availa  
APP C  
moth  
Supp  
each  
also v  
moth  
speci  
Easy  
Syste

Viewer

Support for Q-Flash  
Support for Xpress Install

Bundled Software  
Norton® Internet  
Security (OEM version)

LAN bandwidth  
management software

Operat  
Supp  
64-bi

Form Factor  
Micro ATX Form Factor;  
24.4cm x 24.4cm