

Adapter TP-LINK ARCHER T3U AC1300 Mini Wireless M U-MIMO USB

Šifra: 46085
 Kategorija proizvoda: Ruteri
 Proizvođač: TP-LINK

Cena: **2.413,00** din.

HARDWARE FEATURES	
Interface	USB 3.0
Dimensions (W x D x H)	1.59 × 0.78 × 0.41in. (40.5 × 19.72 × 10.29mm)
Antenna Type	Internal
WIRELESS FEATURES	
Wireless Standards	IEEE 802.11ac, IEEE 802.11a, IEEE 802.11n, IEEE 802.11g, IEEE 802.11b
Frequency	5GHz 2.4GHz
Signal Rate	5GHz 11ac: Up to 867Mbps(dynamic) 11n: Up to 300Mbps(dynamic) 11a: Up to 54Mbps(dynamic) 2.4GHz 11n: Up to 400Mbps(dynamic) 11g: Up to 54Mbps(dynamic) 11b: Up to 11Mbps(dynamic)
Reception Sensitivity	5GHz: 11a 6Mbps: -91dBm 11a 54Mbps: -76dBm 11n HT20: -71dBm 11n HT40: -70dBm 11ac HT20: -68dBm 11ac HT40: -64dBm 11ac HT80: -62dBm 2.4GHz: 11b 11Mbps: -86dBm 11g 54Mbps: -73dBm 11n HT20: -71dBm 11n HT40: -70dBm
Transmit Power	<23dBm (EIRP)
Wireless Modes	Ad-Hoc / Infrastructure Mode
Wireless Security	Support 64/128 bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK
Modulation Technology	DBPSK, DQPSK, CCK, OFDM, 16-QAM, 64-QAM, 256-QAM
OTHERS	
Certification	FCC, RoHS
Package Contents	AC1300 Mini Wireless MU-MIMO USB Adapter Archer T3U Quick Installation Guide Resource CD
System Requirements	Windows 11/10/8.1/8/7/XP, Mac OS X 10.9-10.14
Environment	Operating Temperature: 0?~40? (32?~104?) Storage Temperature: -40?~70? (-40?~158?) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing