

LAN Router TP-LINK TL-WR841N Wireless

LAN Router TP-LINK TL-WR841N Wireless

Šifra: 46146
 Kategorija proizvoda: Ruteri
 Proizvođač: TP-LINK

Cena: **2.595,00** din.

| | |
|---------------------------------|--|
| HARDWARE FEATURES | |
| Interface | 4 10/100Mbps LAN PORTS 1 10/100Mbps WAN PORT |
| Button | Quick Setup Security Button Reset Button |
| External Power Supply | 9VDC / 0.6A |
| Wireless Standards | IEEE 802.11n, IEEE 802.11g, IEEE 802.11b |
| Antenna | 2*5dBi Fixed Omni Directional Antenna |
| Dimensions (W x D x H) | 7.6 x 5.1 x 1.3 in.(192 x 130 x 33 mm) |
| WIRELESS FEATURES | |
| Frequency | 2.4-2.4835GHz |
| Signal Rate | 11n: Up to 300Mbps(dynamic) 11g: Up to 54Mbps(dynamic) 11b: Up to 11Mbps(dynamic) |
| EIRP | <20dBm(EIRP) |
| Reception Sensitivity | 270M: -68dBm@10% PER 130M: -68dBm@10% PER 108M: -68dBm@10% PER 54M: -68dBm@10% PER 11M: -85dBm@8% PER 6M: -88dBm@10% PER 1M: -90dBm@8% PER |
| Wireless Functions | Enable/Disable Wireless Radio, WDS Bridge, WMM, Wireless Statistics |
| Wireless | 64/128/152-bit WEP / WPA / WPA2,WPA-PSK / WPA2-PSK |
| SOFTWARE FEATURES | |
| WAN Type | Dynamic IP/Static IP/PPPoE/ PPTP/L2TP/BigPond |
| DHCP | Server, Client, DHCP Client List, Address Reservation |
| Quality of Service | WMM, Bandwidth Control |
| Port Forwarding | Virtual Server,Port Triggering, UPnP, DMZ |
| Dynamic DNS | DynDns, Comexe, NO-IP |
| VPN Pass-Through | PPTP, L2TP, IPsec (ESP Head) |
| Access Control | Parental Control, Local Management Control, Host List, Access Schedule, Rule Management |
| Firewall Security | DoS, SPI Firewall IP Address Filter/MAC Address Filter/Domain Filter IP and MAC Address Binding |
| Management | Access Control Local Management Remote Management |
| OTHERS | |
| Certification | CE, FCC, RoHS |
| Package Contents | Wireless N Router TL-WR841N Power supply unit Resource CD Quick Installation Guide |
| System Requirements | Microsoft® Windows® 98SE, NT, 2000, XP, Vista™ or Windows 7, MAC® OS, NetWare®, UNIX® or Linux. |
| Environment | Operating Temperature: 0?40? (32104) Storage Temperature: -40?70? (-40158) Operating Humidity: 10%-90% non-condensing |