

Gigabyte Matična ploča AM4 B550 AORUS ELITE V2

Šifra: 47699

Kategorija proizvoda: Matične ploče

Proizvođač: GIGABYTE

Cena: **17.411,00** din.



Tip procesora:

AMD
 AMD® AM4
 AMD® B550
 ATX
 AMD Ryzen™ 5000 Series
 Ryzen™ 5000 G-Series Ryzen™
 4000 G-Series and Ryzen™ 3000
 Series Processors
 DDR4
 Maksimalna ukupna memorija:
 128GB Podržane memorije:
 2.133MHz, 2.400MHz, 2.667MHz,
 2.933MHz, 3.200MHz, 3.300Mhz
 (O.C.), 3.333Mhz (O.C.),
 3.400Mhz (O.C.), 3.466Mhz
 (O.C.), 3.600Mhz (O.C.),
 3.733Mhz (O.C.), 3.800Mhz
 (O.C.), 3.866Mhz (O.C.),
 4.000Mhz (O.C.), 4.400Mhz
 (O.C.), 4.733Mhz (O.C.)
 1 x PCI Express x16 slot
 (PCIEX16), integrated in the
 CPU: - AMD Ryzen™ 5000 Series
 and Ryzen™ 3000 Series
 Processors support PCIe 4.0 x16
 mode - AMD Ryzen™ Ryzen™
 5000 G-Series and Ryzen™ 4000
 G-Series Processors support PCIe
 3.0 x16 mode * For optimum
 performance, if only one PCI
 Express graphics card is to be
 installed, be sure to install it in
 the PCIEX16 slot. 1 x PCI Express
 x16 slot (PCIEX2), integrated in
 the Chipset: - Supporting PCIe
 3.0 x2 mode 1 x PCI Express x16
 slot (PCIEX1_2), integrated in the
 Chipset: - Supporting PCIe 3.0 x1
 mode 1 x PCI Express x1 slot
 (PCIEX1_1), integrated in the
 Chipset: - Supporting PCIe 3.0 x1
 mode
 1 x M.2 connector (M2A_CPU),
 integrated in the CPU, supporting

Podnožje:

Čipset:
 Format ploče:
 Podržani procesori:
 Podržana memorija:

Memorija:

Slotovi za proširenje:

Storage:

Socket 3, M key, type 22422260228022110 SSDs: - AMD Ryzen™ 5000 Series and Ryzen™ 3000 Series Processors support SATA and PCIe 4.0 x4x2 SSDs - AMD Ryzen™ Ryzen™ 5000 G-Series and Ryzen™ 4000 G-Series Processors support SATA and PCIe 3.0 x4x2 SSDs 1 x M.2 connector (M2B_SB), integrated in the Chipset, supporting Socket 3, M key, type 22422260228022110 SSDs: - Supporting SATA and PCIe 3.0 x4x2 SSDs 4 x SATA 6Gbs connectors, integrated in the Chipset: - Support for RAID 0, RAID 1, and RAID 10

Mrežna karta:

Realtek® 2.5GbE LAN chip (2.5 Gbit1 Gbit100 Mbit)

Zvučna karta:

Realtek® ALC1200 codec High Definition Audio 245.17.1-

USB:

Chipset: 2 x USB 3.2 Gen 2 Type-A ports (red) on the back panel 2 x USB 3.2 Gen 1 ports on the back panel Chipset: 1 x USB Type-C™ port with USB 3.2 Gen 1 support, available through the internal USB header 1 x USB 3.2 Gen 1 ports (Red) 2 x USB 3.2 Gen 1 ports 2 x USB 2.0 1 ports 1 x Q-Flash Plus port on the back panel 2 x USB 3.2 Gen 1 ports available through the internal USB header 5 x audio jacks 2 x USB 2.0 1 ports on the back panel Chipset+USB 2.0 Hub: 4 x USB 2.0 1 ports available through the internal USB headers

Konektori na zadnjoj strani:

1 x DisplayPort 1 x HDMI port 2 x USB 3.2 Gen 2 Type-A ports (Red) 3 x USB 3.2 Gen 1 ports 2 x USB 2.0 1 ports 1 x Q-Flash Plus port on the back panel 2 x USB 3.2 Gen 1 ports available through the internal USB header 5 x audio jacks 2 x USB 2.0 1 ports on the back panel Chipset+USB 2.0 Hub: 4 x USB 2.0 1 ports available through the internal USB headers

Interni konektori:

1 x 24-pin ATX main power connector 1 x 8-pin ATX 12V power connector 2 x M.2 Socket 3 connectors 4 x SATA 6Gbs connectors 1 x CPU fan header 1 x water cooling CPU fan header 3 x system fan headers 1 x CPU cooler LED strip RGB LED strip headers 2 x M-DEF BIOS pin 1.0a headers 2 x RGB LED strip headers 1 x M2B_L5M strip headers 1 x front panel header 1 x front panel audio header 1 x USB Type-C™ port, with USB 3.2 Gen 1 support 1 x USB 3.2 Gen 1 header 2 x USB 2.0 1 headers 1 x Trusted Platform Module (TPM) header (2x6 pin, for the GC-TPM2.0_S module only) 1 x Clear CMOS jumper

Bios:

1 x 256 Mbit flash - Use of licensed AMI UEFI BIOS with 1.0a headers 2 x M2B_L5M strip headers 1 x front panel header 1 x front panel audio header 1 x USB Type-C™ port, with USB 3.2 Gen 1 support 1 x USB 3.2 Gen 1 header 2 x USB 2.0 1 headers 1 x Trusted Platform Module (TPM) header (2x6 pin, for the GC-TPM2.0_S module only) 1 x Clear CMOS jumper

Razno:

{"url":"","title":"","target":""}