

GIGABYTE B550M DS3H matična ploča

Šifra: 53143

Kategorija proizvoda: Matične ploče

Proizvođač: GIGABYTE

Cena: **12.083,00** din.



Tip procesora:

AMD
 AMD® AM4
 AMD® B550
 Micro ATX
 AMD podnožje AM4, podržava:
 3rd Generation AMD Ryzen
 procesore 3rd Generation AMD
 Ryzen sa Radeon grafičkim
 procesorima
 DDR4
 - 4 x DDR4 DIMM podnožje
 podržava do 128 GB (32 GB
 single DIMM capacity) sistemske
 memorije - 3rd Gen AMD Ryzen
 procesore: - Podržava DDR4
 4400(O.C.) 4000(O.C.)
 3600(O.C.) 3333(O.C.)
 32002933266724002133 MHz
 memorijske module - 3rd Gen
 AMD Ryzen sa Radeon grafičkim
 procesorima: - Podržava DDR4
 4733(O.C.) 4600(O.C.)
 4400(O.C.) 4000(O.C.)
 3600(O.C.) 3333(O.C.)
 32002933266724002133 MHz
 memorijske module - Dual
 channel memory architecture -
 Podržava ECC Un-buffered DIMM
 1Rx82Rx8 memorijske module -
 Podržava non-ECC Un-buffered
 DIMM 1Rx82Rx81Rx16
 memorijske module - Podržava
 Extreme Memory Profile (XMP)
 memory modules
 Integrated in the 3rd Generation
 AMD Ryzen sa Radeon grafičkim
 procesorima: - 1 x DVI-D port,
 podržava maksimalnu rezoluciju
 od 1920x1200@60 Hz - DVI-D
 port ne podržava D-Sub
 konekciju putem adaptera - 1 x
 HDMI port, podržava maksimalnu
 rezoluciju od 4096x2160@60
 Hz - Podržava HDMI 2.1 verziju,

Podnožje:

Čipset:

Format ploče:

Podržani procesori:

Podržana memorija:

Memorija:

Integrirana grafička karta:

HDCP 2.3, i HDR - Maksimalna deljena memorija 16 GB

Slotovi za proširenje:

Storage:

Mrežna karta:

Zvučna karta:

USB:

Konektori na zadnjoj strani:

Interni konektori:

1 x PCI Express x16 slot (PCIEX16), integrisan u CPU: - 3rd Generation AMD Ryzen CPU, procesor podržava PCIe 4.0 x16 podnožje, Generation AMD Ryzen 3000/2000/1000 grafičkim procesorima AMD Ryzen PCIe 3.0 x16 procesor podržava PCIe Express PCIe 4.0 x16 x4 PCIe 4.0 integriran AMD Ryzen Radeon™ Radeon™ grafičkim procesorima PCIe Express SATA (PCIEX.0) x4 x2019s u Chipset: - Podržava PCIe 3.0, integrisan u Chipset, podržava podnožje 3, M key, tip 224222602280 SSDs: - Podržava SATA i PCIe 3.0 SSDs (100 MB/s SATA 6Gbs connectors, integrisani u Chipset: - Podržava RAID 0, RAID 1, i RAID 10

- Realtek ALC887 codec - High Definition Audio - 245.17.1-Channel CPU: 4 x USB 3.2 Gen 1 porta na zadnjem panelu Chipset: - 2 x USB 3.2 Gen 1 porta dostupni putem internog USB headera - 1 x PS/2 keyboard/mouse port - 1 x DVI-D port - 1 x HDMI port - 4 x USB 3.2 Gen 1 porta - 4 x USB 2.0 1.1 porta - 1 x RJ-45 port - 3 x audio jacks

- 1 x 24-pin ATX main power connector - 1 x 8-pin ATX 12V power connector - 1 x CPU fan header - 2 x system fan headers - 2 x addressable LED strip headers - 2 x RGB LED strip headers - 1 x CPU cooler LED stripRGB LED strip header - 2 x M.2 Socket 3 connectors - 4 x SATA 6Gbs connectors - 1 x front panel header - 1 x front panel audio header - 1 x USB 3.2 Gen 1 header - 1 x USB 2.0 1.1 header - 1 x Trusted Platform Module (TPM) header (2x6 pin, for the GC-TPM2.0_S module only) - 1 x serial port header - 1 x Clear CMOS jumper - 1 x Q-Flash Plus

button

Bios:

Razno:

- 1 x 256 Mbit flash - Use of
licensed AMI UEFI BIOS - PnP,
1.0a, DMI 2.7, WfM 2.0, SM BIOS
2.7, ACPI 5.0