

IYAMA The TE5512MIS-B3AG is an exceptional 4K UHD interactive display to enhance collaboration, communication, and engagement.



Šifra: 58913
 Kategorija proizvoda: Monitori i oprema
 Proizvođač: IYAMA

Cena: **236.735,00** din.

Display Type:	LCD	Display Technology:
	TFT Active Matrix	Diagonal Length:
	55"	Viewable Display Diagonal Length:
	55"	Type of Matrix:
	IPS	Pitch Type:
	Dot Pitch	Pitch Width:
	0.315 mm	Color Support:
	1.07B	Maximum Resolution:
	3840x2160	Maximum Horizontal Scan Frequency:
	135 kHz	Minimum Horizontal Scan Frequency:
	30 kHz	Image Brightness:
	400 cdm ²	Dynamic Contrast Ratio:
	4 000 : 1	Image Contrast:
	1 200 : 1	Image Max. H-View Angle:
	178 °	Image Max. V-View Angle:
	178 °	Response Time:
	8 ms	Display Surface:
	Matt Type	Screen Treatment:
	Anti-Glare, Hard Coating 7H	Image Aspect Ratio:
	16:9	Display Features:
	HDCP Ready, Direct LED, UHD, Low Blue Light, 40 Point Touch-	

Speaker Form Factor:	Integrated
Audio Output Mode:	Stereo
Output Power per Channel:	16 W
Output Power:	32 W
VGA:	1 (15-pin D-sub)
HDMI:	4 (HDMI (Type A))
Audio Interface:	2 (3.5-mm minijack)
USB 3.2 Gen 1:	1 (USB 3.1 (type C))
Serial:	1 (RS-232)
LAN:	3 (RJ-45)
Infrared:	1
SPDIF-out Optical:	1 (TOSLINK)
USB 3.2:	4 (USB 3.2 (type A))
Power Device Type:	Power Supply
Power Device Location:	Internal
Maximum Input Frequency:	60 Hz
Maximum Input Voltage:	240 V
Minimum Input Frequency:	50 Hz
Minimum Input Voltage:	100 V
Power Consumption Operational:	111 W
Power Consumption Stand BySleep:	0.5 W
Built-in Devices:	Wi-Fi Adapter, Light Sensor, Bluetooth
Cable Included:	Power Cable, USB Cable, HDMI Cable
Included Accessories:	Remote Control, Quick Start Guide, Safety Sheet, 4 x Touch Pen
Mounting Capability:	Wallmount
Flat Display Mounting Interface:	400x200mm
Monitor Compliant Standards:	Plug and Play, VESA DDC 2B, VESA FDMI, RoHS, REACH
External Color:	Black
Mean Time Between Failures:	50000 hr
CPU:	ARM Cortex-A55, 4cores,
GPU:	Mali-G52
Memory:	8 GB SDRAM
Storage Capacity:	64 GB
Maximum Operating Ambient Temperature:	40 °C
Minimum Operating Ambient Temperature:	0 °C
Maximum Non-Operating Ambient Temperature:	60 °C
Minimum Non-Operating	

Ambient Temperature:

-20 °C

87 mm

774 mm

1271 mm

26.1 kg

Yes

36 month(s)

Serial Number

87 mm

1271 mm

774 mm

34.5 kg

26.1 kg

1

220 mm

1401 mm

859 mm

34.5 kg

6 kg

2.4 kg

1

1

Box

4948570123681

Depth (mm):

Height (mm):

Width (mm):

Nominal Weight:

Warranty Products Returnable:

Warranty Term (month):

Warranty validation Criteria:

Pack Length (mm):

Pack Width (mm):

Pack Height (mm):

Pack Weight Brutto (kg):

Pack Weight Netto (kg):

Pieces in pack:

Box Length (mm):

Box Width (mm):

Box Height (mm):

Box Weight Brutto (kg):

Retail Packaging Net Weight

Carton
Retail Packaging Net Weight

Plastic:

Packs in Box:

Packs per Pallet:

Package Type:

EAN Code: