

IYAMA 55" iiWare10 , Android 11, 40-Points PureTouch IR with zero bonding, 3840x2160, UHD IPS panel, Metal Housing, Fan-less, Speakers 2x 16W



Šifra: 58914
 Kategorija proizvoda: Monitori i oprema
 Proizvođač: IYAMA

Cena: **188.537,00** din.

Display Type: LCD
 TFT Active Matrix
 55"
 55"
 IPS
 Dot Pitch
 0.315 mm
 1.07B
 3840x2160
 135 kHz
 30 kHz
 400 cdm²
 4 000 : 1
 1 200 : 1
 178 °
 178 °
 8 ms
 Matt Type
 Anti-Glare, Hard Coating 7H,
 Haze 25%
 16:9
 Touch-screen, HDCP Ready,
 Direct LED, UHD, Low Blue Light,

Display Technology:
 Diagonal Length:
 Viewable Display Diagonal Length:
 Type of Matrix:
 Pitch Type:
 Pitch Width:
 Color Support:
 Maximum Resolution:
 Maximum Horizontal Scan Frequency:
 Minimum Horizontal Scan Frequency:
 Image Brightness:
 Dynamic Contrast Ratio:
 Image Contrast:
 Image Max. H-View Angle:
 Image Max. V-View Angle:
 Response Time:
 Display Surface:
 Screen Treatment:
 Image Aspect Ratio:
 Display Features:

Speaker Form Factor:	Integrated
Audio Output Mode:	Stereo
Output Power per Channel:	16 W
Output Power:	32 W
VGA:	1 (15-pin D-sub)
HDMI:	4 (HDMI (Type A))
Audio Interface:	2 (3.5-mm minijack)
USB 3.1:	1 (USB 3.1 (type C))
Serial:	1 (RS-232)
LAN:	3 (RJ-45)
Infrared:	1
SPDIF-out Optical:	1 (TOSLINK)
USB 3.0:	4 (USB 3.0 (Type A))
Power Device Type:	Power Supply
Power Device Location:	Internal
Maximum Input Frequency:	60 Hz
Maximum Input Voltage:	240 V
Minimum Input Frequency:	50 Hz
Minimum Input Voltage:	100 V
Power Consumption Operational:	105 W
Power Consumption Stand BySleep:	0.5 W
Built-in Devices:	Wi-Fi Adapter, Light Sensor, Bluetooth
Cable Included:	Power Cable, USB Cable, HDMI Cable
Included Accessories:	Remote Control, Quick Start Guide, Safety Sheet, 4 x Touch Pen
Mounting Capability:	Wallmount
Flat Display Mounting Interface:	400x200mm
Monitor Compliant Standards:	Plug and Play, VESA FDMI, RoHS, BEACH
External Color:	Black
Mean Time Between Failures:	50000 hr
CPU:	ARM Cortex-A55, 4cores,
GPU:	Mali-G52
Memory:	4 GB SDRAM
Storage Capacity:	32 GB
Maximum Operating Ambient Temperature:	40 °C
Minimum Operating Ambient Temperature:	0 °C
Maximum Non-Operating Ambient Temperature:	60 °C
Minimum Non-Operating	

Ambient Temperature:

-20 °C

87 mm

744 mm

1271 mm

26.1 kg

Yes

36 month(s)

Serial Number

1401 mm

220 mm

859 mm

34.5 kg

26.1 kg

1

1401 mm

220 mm

859 mm

34.5 kg

8.1 kg

0.3 kg

1

Box

4948570121908

Depth (mm):

Height (mm):

Width (mm):

Nominal Weight:

Warranty Products Returnable:

Warranty Term (month):

Warranty validation Criteria:

Pack Length (mm):

Pack Width (mm):

Pack Height (mm):

Pack Weight Brutto (kg):

Pack Weight Netto (kg):

Pieces in pack:

Box Length (mm):

Box Width (mm):

Box Height (mm):

Box Weight Brutto (kg):

Retail Packaging Net Weight

Carton
Retail Packaging Net Weight

Plastic:

Packs in Box:

Package Type:

EAN Code: