

TE6512MIS-B3AG is an exceptional 4K UHD interactive display designed by iiyama to enhance collaboration, communication, and engagement.



Šifra: 58927

Kategorija proizvoda: Monitori i oprema

Proizvođač: IIYAMA

Cena: **241.532,00** din.

Display Type:

LCD  
 TFT Active Matrix  
 65"  
 65"

IPS  
 Dot Pitch  
 0.372 mm  
 1.07B  
 3840x2160  
 135 kHz  
 30 kHz

400 cdm<sup>2</sup>  
 4 000 : 1  
 1 200 : 1  
 178 °  
 178 °  
 8 ms  
 Matt Type  
 Anti-Glare, Hard Coating 7H  
 16:9  
 LED Backlight, HDCP Ready,  
 UHD, Low Blue Light, 40 Point  
 Touch-Screen, Operating Mode -

Display Technology:

Diagonal Length:  
 Viewable Display Diagonal  
 Length:  
 Type of Matrix:

Pitch Type:  
 Pitch Width:  
 Color Support:  
 Maximum Resolution:  
 Maximum Horizontal Scan  
 Frequency:  
 Minimum Horizontal Scan  
 Frequency:  
 Image Brightness:

Dynamic Contrast Ratio:  
 Image Contrast:  
 Image Max. H-View Angle:  
 Image Max. V-View Angle:  
 Response Time:  
 Display Surface:  
 Screen Treatment:  
 Image Aspect Ratio:  
 Display Features:

Speaker Form Factor:	Integrated
Audio Output Mode:	Stereo
Output Power per Channel:	16 W
Output Power:	32 W
VGA:	1 (15-pin D-sub)
HDMI:	4 (HDMI (Type A))
Audio Interface:	2 (3.5-mm minijack)
Serial:	1 (RS-232)
LAN:	3 (RJ-45)
Infrared:	1
SPDIF-out Optical:	1 (TOSLINK)
USB 3.2 Gen 1:	4 (USB 3.2 (type A)); 1 (USB 3.2 (type C))
Power Device Type:	Power Supply
Power Device Location:	Internal
Maximum Input Frequency:	60 Hz
Maximum Input Voltage:	240 V
Minimum Input Frequency:	50 Hz
Minimum Input Voltage:	100 V
Power Consumption Operational:	138 W
Power Consumption Stand BySleep:	0.5 W
Built-in Devices:	Wi-Fi Adapter, Light Sensor, Bluetooth, USB Media Player
Cable Included:	Power Cable, USB Cable, HDMI Cable
Included Accessories:	Remote Control, Quick Start Guide, Safety Sheet, 4 x Touch Pen
Mounting Capability:	Wallmount
Flat Display Mounting Interface:	600x400mm
Monitor Compliant Standards:	Plug and Play, VESA DDC 2B, VESA FDMI, RoHS, REACH
External Color:	Black
Mean Time Between Failures:	50000 hr
CPU:	ARM Cortex-A55, 4cores,
GPU:	Mali-G52
Memory:	8 GB RDRAM
Storage Capacity:	64 GB
Maximum Operating Ambient Temperature:	40 °C
Minimum Operating Ambient Temperature:	0 °C
Maximum Non-Operating Ambient Temperature:	60 °C
Minimum Non-Operating	

Ambient Temperature:

-20 °C  
87.5 mm  
896.5 mm  
1488.5 mm  
35 kg  
1780007  
Yes  
36 month(s)  
Serial Number  
87 mm  
1488 mm  
896 mm  
44.7 kg  
35 kg  
1  
208 mm  
1628 mm  
1005 mm  
44.7 kg  
6.7 kg  
  
3 kg  
  
1  
1  
Box  
4948570123698

Depth (mm):  
Height (mm):  
Width (mm):  
Nominal Weight:  
EPREL:  
Warranty Products Returnable:  
Warranty Term (month):  
Warranty validation Criteria:  
Pack Length (mm):  
Pack Width (mm):  
Pack Height (mm):  
Pack Weight Brutto (kg):  
Pack Weight Netto (kg):  
Pieces in pack:  
Box Length (mm):  
Box Width (mm):  
Box Height (mm):  
Box Weight Brutto (kg):  
Retail Packaging Net Weight  
Carton  
Retail Packaging Net Weight  
Plastic:  
Packs in Box:  
  
Packs per Pallet:  
Package Type:  
EAN Code: