

TE6512MIS-B3AG is an exceptional 4K UHD interactive display designed by iiyama to enhance collaboration, communication, and engagement.



Šifra: 58927
 Kategorija proizvoda: Monitori i oprema
 Proizvođač: IIYAMA

Cena: **262.493,00** din.

<p>Display Type:</p> <p>LCD</p> <p>TFT Active Matrix</p> <p>65"</p> <p>65"</p> <p>IPS</p> <p>Dot Pitch</p> <p>0.372 mm</p> <p>1.07B</p> <p>3840x2160</p> <p>135 kHz</p> <p>30 kHz</p> <p>400 cdm²</p> <p>4 000 : 1</p> <p>1 200 : 1</p> <p>178 °</p> <p>178 °</p> <p>8 ms</p> <p>Matt Type</p> <p>Anti-Glare, Hard Coating 7H</p> <p>16:9</p> <p>LED Backlight, HDCP Ready, UHD, Low Blue Light, 40 Point Touch-Screen, Operating Mode -</p>	<p>Display Technology:</p> <p>Diagonal Length:</p> <p>Viewable Display Diagonal Length:</p> <p>Type of Matrix:</p> <p>Pitch Type:</p> <p>Pitch Width:</p> <p>Color Support:</p> <p>Maximum Resolution:</p> <p>Maximum Horizontal Scan Frequency:</p> <p>Minimum Horizontal Scan Frequency:</p> <p>Image Brightness:</p> <p>Dynamic Contrast Ratio:</p> <p>Image Contrast:</p> <p>Image Max. H-View Angle:</p> <p>Image Max. V-View Angle:</p> <p>Response Time:</p> <p>Display Surface:</p> <p>Screen Treatment:</p> <p>Image Aspect Ratio:</p> <p>Display Features:</p>
---	--

Speaker Form Factor:	Integrated
Audio Output Mode:	Stereo
Output Power per Channel:	16 W
Output Power:	32 W
VGA:	1 (15-pin D-sub)
HDMI:	4 (HDMI (Type A))
Audio Interface:	2 (3.5-mm minijack)
Serial:	1 (RS-232)
LAN:	3 (RJ-45)
Infrared:	1
SPDIF-out Optical:	1 (TOSLINK)
USB 3.2 Gen 1:	4 (USB 3.2 (type A)); 1 (USB 3.2 (type C))
Power Device Type:	Power Supply
Power Device Location:	Internal
Maximum Input Frequency:	60 Hz
Maximum Input Voltage:	240 V
Minimum Input Frequency:	50 Hz
Minimum Input Voltage:	100 V
Power Consumption Operational:	138 W
Power Consumption Stand BySleep:	0.5 W
Built-in Devices:	Wi-Fi Adapter, Light Sensor, Bluetooth, USB Media Player
Cable Included:	Power Cable, USB Cable, HDMI Cable
Included Accessories:	Remote Control, Quick Start Guide, Safety Sheet, 4 x Touch Pen
Mounting Capability:	Wallmount
Flat Display Mounting Interface:	600x400mm
Monitor Compliant Standards:	Plug and Play, VESA DDC 2B, VESA FDMI, RoHS, REACH
External Color:	Black
Mean Time Between Failures:	50000 hr
CPU:	ARM Cortex-A55, 4cores,
GPU:	Mali-G52
Memory:	8 GB RDRAM
Storage Capacity:	64 GB
Maximum Operating Ambient Temperature:	40 °C
Minimum Operating Ambient Temperature:	0 °C
Maximum Non-Operating Ambient Temperature:	60 °C
Minimum Non-Operating	

Ambient Temperature:

-20 °C

87.5 mm

896.5 mm

1488.5 mm

35 kg

1780007

Yes

36 month(s)

Serial Number

87 mm

1488 mm

896 mm

44.7 kg

35 kg

1

208 mm

1628 mm

1005 mm

44.7 kg

6.7 kg

3 kg

1

1

Box

4948570123698

Depth (mm):

Height (mm):

Width (mm):

Nominal Weight:

EPREL:

Warranty Products Returnable:

Warranty Term (month):

Warranty validation Criteria:

Pack Length (mm):

Pack Width (mm):

Pack Height (mm):

Pack Weight Brutto (kg):

Pack Weight Netto (kg):

Pieces in pack:

Box Length (mm):

Box Width (mm):

Box Height (mm):

Box Weight Brutto (kg):

Retail Packaging Net Weight

Carton Retail Packaging Net Weight

Plastic:

Packs in Box:

Packs per Pallet:

Package Type:

EAN Code: